

1. PRODUCT NAME

Petrobond

2. MANUFACTURER

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241

Phone: 513-733-1000
Toll Free: 800-543-7077
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com

- **Rapid Drying:** In just minutes you can sealcoat.
- **Insures Bonding:** Penetrating surfactant package provides maximum bond to oil stains and sealer.
- **Prevents Bleeding:** The tough copolymers provide maximum shield against bleeding.
- **Versatile:** Can be used to de-tack fresh hot applied sealants.

3. PRODUCT DESCRIPTION

Petrobond is a blend of copolymers and surfactants. It seals oil, gas, grease and chemical stained areas on asphalt pavements.

Packaging:

Available in 5 gal. pails.

Color:

Petrobond is light gray as a liquid and dries clear.

Basic Uses:

Petrobond is an oil spot primer formulated to ensure adhesion of pavement sealer to oil, gas, grease and chemical stained areas on asphalt pavements. It may be used as a primer for new asphalt patches. Petrobond can also be used to de-tack fresh hot applied crack and joint sealant.

Composition:

As shipped, Petrobond is a water-based oil spot primer.

Limitations:

Do not allow to freeze. Do not store in direct sunlight or where temperature exceeds 120°F.

4. INSTALLATION

Preparatory Work:

The areas to be treated must be free of dirt and grime. Scrape away build-up of oil, gas and/or grease deposits before priming.

Methods:

Application of Petrobond by spray is recommended. Can also be brushed or rolled.

Mix Design:

Use full strength, do not dilute.

Application:

The coverage rate will vary depending on the condition of pavement and on the application method. Rough surface will consume more when applied with a roller or brush.

Precautions:

Keep out of reach of children. Close container when not in use.

5. MAINTENANCE

Tools and equipment may be cleaned promptly with water.

6. TECHNICAL DATA

Environmental Considerations:

Petrobond is considered non-hazardous when tested according to the EPA's TCLP (Toxicity Characteristic Leaching Procedure). Petrobond is a water-based material containing less than 50g/L (.42 lbs./gal.) VOC content.

7. TECHNICAL SERVICE

Material safety data sheets, product and application recommendations, as well as assistance with special situations and field service are available upon request.

8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Neyra Industries, Inc. guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, workmanship and equipment are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of Neyra Industries, Inc. exceed the purchase price of the shipped materials.

9. ADDITIONAL INFORMATION

Neyra Industries, Inc. manufactures a full line of asphalt pavement maintenance and recreational surface products as well as application equipment sold and distributed nationally at our plants and through distributors. To find the supplier most convenient to you, please contact us.

NEYRA

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241

Phone: 513-733-1000
Toll Free: 800-543-7077
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com